



SPECIAL PRODUCTS

ADDINOL POLE PROTECTION SPRAY

PRODUCT DESCRIPTION

ADDINOL Pole Protection Spray is based on an organic solvent, mineral oil and additives.

Optimal temperature for application and storage from +10°C up to +25°C.

APPLICATION

- Designed for cleaning and protecting battery poles, connecting terminals, battery holder and grounds

DELIVERY

Delivery in 150 ml aerosol cans (12 pieces / carton).

HANDLING


1. Shake can well before use.
2. The surfaces to be treated have to be cleaned of traces of acid and corrosion products and dried thoroughly.
3. Spraying distance approx. 20 to 30 cm, ensure complete wetting.
4. Ventilation time 5 minutes at room temperature.

CHARACTERISTICS

- Eliminates corrosion and prevents its formation
- Displaces humidity
- Very good solvency for mixtures of greases, oil and humid soil
- Good compatibility with common wire enamels and plastics (not suitable for acrylonitrile butadiene styrene and polystyrole)
- Protection against leakage currents and power loss
- Chlorine-free propellant based on a propane / butane mixture

ADVANTAGES AND BENEFITS

- Protection of machine parts
- Increases lifetime of battery
- Prevents the formation of corrosion
- Efficient cleaning; protection against leakage current
- Long lifetime of insulating materials
- Guarantee a permanent and trouble-free operation
- Ozone-friendly





ADDINOL POLE PROTECTION SPRAY

SPECIFICATIONS AND TYPICAL PARAMETERS

Feature	Test condition / unit		Pole Protection Spray	Method acc. to
Colour			deep blue	visual
Odour			solvent like	olfactory
Density – active agent	at 20°C	kg/m ³	725	DIN 51757
Density - mixture	at 20°C	kg/m ³	610	DIN 51757
Flash point	COC	°C	< -20	DIN EN ISO 2592
Ignition temperature		°C	< 200	DIN 51794

ADDINOL - The Experts for High-Performance Lubricants

We at ADDINOL develop and produce more than 600 high-performance lubricants of the new generation. Among these are automotive lubricants for highest demands and pioneering developments for industrial applications. Our customers all over the world benefit from the high and stable quality of our ADDINOL high-performance lubricants, our know-how and the individual customer advisory service of our competent experts. Our company has world wide activities. ADDINOL high-performance lubricants are distributed by more than 90 international partners.

The data given in this product sheet represent our current level of knowledge and experience. Due to the various specific application they do, however, not discharge the user from his own examination. The information provided herein may not be used to derive a legally binding warranty of specific properties or the suitability for a certain purpose of application. Detailed security-concerning and toxicological data as well as security instructions for each product can be taken from the corresponding Material Safety Data Sheets (MSDS). High-performance lubricants from ADDINOL are under continuous development. Therefore, ADDINOL Lube Oil GmbH keeps the right to change technical data in this product data sheet without notification. In case of doubt, please do not hesitate to contact our customers' advisory service.

Am Haupttor, D-06237 Leuna, Germany
Phone: +49 (0) 3461-845-201, Fax: +49 (0) 3461-845-555
E-Mail: info@addinol.de, Internet: www.addinol.de