



LUBRICANTS FOR FOOD INDUSTRY

ADDINOL FOODPROOF VDL 32 S, 46 S, 68 S, 100 S, 150 S

PRODUCT DESCRIPTION

ADDINOL FoodProof VDL ... S are high-performance compressor oils based on PAO. The products are characterised by its neutral smell and light colour.

All ingredients of ADDINOL FoodProof VDL ... S are physiologically harmless and meet the European guidelines, the NSF category H1 as well as the requirements acc. to Kosher and Halal. The ingredients also meet the internationally accepted FDA standards and they are free from allergens acc. to Regulation (EU) No. 1169/2011, annex II.

Application temperature from -35°C up to +120°C.

APPLICATION

- Excellent suitability for the lubrication of compressors of all construction types at airtend temperatures up to +220 °C
- In particular for screw-type and sliding-vane compressors
- Ideal for applications in food, feed, cosmetics as well in pharmaceutical industry with high requirements on the lubricant
- Highly recommended for lubrication points where an incidental contact with food cannot be excluded

APPROVALS / SPECIFICATIONS

Listed and approved acc. to:

- NSF-H1 (please see page 2 for registration numbers)
- Kosher
- Halal

Meet the purity requirements according to:

- 21 CFR 178.3570 (FDA)

Meet and surpass the requirements of the specification according to:

- DIN ISO 3448
- DIN 51506 (VDL)

DELIVERY

Delivery preferable in drums and 20L cans.

PLEASE NOTE

An overlubrication is to be avoided to prevent an unnecessary pollution of food and commodities.

CHARACTERISTICS

- Light colour; neutral in smell and taste, physiologically harmless; NSF-H1 registered
- Efficient AW additivation
- Reliable corrosion protection
- Neutral towards common sealing materials and paints
- Excellent air and water separation; low foaming tendency
- High oxidation stability

ADVANTAGES AND BENEFITS

- Highly recommended for lubrication points where an incidental contact with food cannot be excluded
- Effective wear protection
- Also usable for higher requirements on the lubricant
- Excellent protection of machine parts and trouble-free operation
- Outstanding protection towards leakages due to a long lifetime of the sealing material
- Excellent safety against cavitations and foam formation
- Reduction of operating costs by extending the oil operating life





ADDINOL FOODPROOF VDL 32 S, 46 S, 68 S, 100 S, 150 S

SPECIFICATIONS AND TYPICAL PARAMETERS

Feature	Test condition / unit		ADDINOL FoodProof VDL					Method acc. to
			32 S	46 S	68 S	100 S	150 S	
ISO viscosity grade			32	46	68	100	150	DIN ISO 3448
Application temperature		°C	-35 up to +120					
NSF registration number			154562	154563	154564	154565	154566	
Density	at 15°C	kg/m ³	836	839	841	844	846	DIN 51757
Viscosity	at 40°C	mm ² /s	32.5	44.9	65.6	100	158	ASTM D 7042
	at 100°C	mm ² /s	6.1	7.7	10.6	15.0	22.4	
Viscosity index			138	139	152	157	169	DIN ISO 2909
Flash point	COC	°C	260			270	280	DIN EN ISO 2592
Pour point		°C	-60	-55				ASTM D 7346
Corrosion protection on steel	Method A	corr.level	passed					DIN ISO 7120
Corrosivity on copper	at 100°C, 3h	corr.level	1					DIN EN ISO 2160
Air separation capacity	at 50°C	Min	< 3	< 3	< 5	< 10	< 20	DIN ISO 9120
Carbon residue after ageing		wt-%	≤ 0.1					DIN 51352-2
Foaming characteristics	at 24°C	ml/ml	< 75/0					ASTM D 892
	at 93.5°C	ml/ml	0/0					
	at 24°C nach 93.5°C	ml/ml	< 75/0					

ADDINOL - The Experts for High-Performance Lubricants

We at ADDINOL develop and produce more than 600 high-performance lubricants of the new generation. Among these are automotive lubricants for highest demands and pioneering developments for industrial applications. Our customers all over the world benefit from the high and stable quality of our ADDINOL high-performance lubricants, our know-how and the individual customer advisory service of our competent experts. Our company has world wide activities. ADDINOL high-performance lubricants are distributed by more than 90 international partners.

The data given in this product sheet represent our current level of knowledge and experience. Due to the various specific application they do, however, not discharge the user from his own examination. The information provided herein may not be used to derive a legally binding warranty of specific properties or the suitability for a certain purpose of application. Detailed security-concerning and toxicological data as well as security instructions for each product can be taken from the corresponding Material Safety Data Sheets (MSDS). High-performance lubricants from ADDINOL are under continuous development. Therefore, ADDINOL Lube Oil GmbH keeps the right to change technical data in this product data sheet without notification. In case of doubt, please do not hesitate to contact our customers' advisory service.